

ADVANCED PATIO AND BLOCK PAVING CLEANER

Thompson's Advanced Patio and Block Paving Cleaner is a water based treatment for the effective removal of dirt, mould and algae from patio and block paving. It will also prevent moss & mould re-growth on the surface for 6 months.



COMPOSITION

Contains 2% w/w benzalkonium chloride (20g/l) and surface active agents as a solution in water.

PROPERTIES

Appearance - Slightly hazy, low viscosity liquid.
Colour - Colourless.
Odour - Low, inoffensive.
Solubility - Miscible with water.
Flash Point (°C) - > 60CC.

AREAS OF APPLICATION

Patio & paving slabs, block paving, flag stones, concrete, tarmac, red bricks, tiles & terracotta.

PREPARATION

Give the surface a scrub with a stiff bristle brush to remove any dust or dirt.

APPLICATION

Pour the cleaner onto the surface and give the area a good scrub with a stiff bristle brush.
Leave it for 15 minutes and then give the area another scrub.

Hose down and wash off the suds.

Leave to dry.

Maintain your patio and repeat this process after 6 months to stop mould and algae re-growth.

COVERAGE

Thompson's Advanced Patio and Block Paving Cleaner will cover 4m² per litre.

Coverage rates may vary depending on the texture and type of surface you're coating. The level quotes is based on average performance. A site trial is recommended.

CLEANING OF TOOLS

Remove as much product as possible from application equipment before cleaning.

Clean brushes, sprays or watering cans immediately after use with water.

DRY TIME

Thompson's Advanced Patio & Block Paving Cleaner will be dry in 30 minutes. Dry times will vary depending on the texture and type of surface being treated. Ensure the surface is dry before protecting with your chosen seal.

IMPORTANT NOTES

- This product may change the colour & appearance of your patio. Always test an inconspicuous area first before cleaning the whole area.
- Ingrained stains may not completely vanish after application of this cleaner. For heavy duty stains use Thompson's Oil & Drive Cleaner.
- Take care when cleaning, as surfaces may become slippery when wet.
- Avoid spillage onto surrounding vegetation.

STORAGE

Observe label precautions. Store between 5 and 25°C. Keep in a cool, dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Containers which are opened should be properly resealed and kept upright to prevent leakage.

To avoid risk of spillage always store and transport in a secure and upright position.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flash point above 60°C.
Non-flammable product.

SUPPLY

Obtainable from most paint suppliers, DIY outlets and builders' merchants.

SIZES

5L.

DISPOSAL

Do not empty left over product into drains or watercourses.

Some local authorities have special ways to get rid of waste coatings.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Thompson's product are available on request from our Technical Services Department.