

## ROOF & GUTTER SEALANT

**Thompson's Roof & Gutter Sealant provides a long lasting, highly flexible repair to roofs & gutters. It can be used to repair cracks, rips, joints and general leaks and can be applied direct to damp surfaces.**

### COMPOSITION

A solution of mineral rubber/binder in a mixed solvent.

### PROPERTIES

Appearance – Sealant containing a black viscous liquid.

VOC Content – Very High (>50% w/v)

Odour – Characteristic of bitumen.

Solubility – Immiscible with water.

### AREAS OF APPLICATION

Suitable for use on roofing felt, pipes & guttering.

### PREPARATION

Remove dirt or algae with a stiff brush. Pack any deep gaps, if required.

### APPLICATION

Cut the nozzle at a 45 degree angle to a width matching the gap you're going to seal. Fit the cartridge into a standard sealant gun. Apply slowly and evenly at an angle to the repair, making sure it covers both side of the repair. If you're joining gutters, apply sealant to both surfaces and press them together. Smooth down with a wetted spatula. The product may remain tacky after a few hours of application, so don't touch it.

### DRYING TIME

The drying time for Thompson's Roof & Gutter Repair will vary dependent upon the nature of the substrate and the thickness of the coating applied. It will however, stop the leak immediately. Allow to dry naturally.

### COVERAGE

Coverage depends on the number and thickness of the coats applied.

### CLEANING OF TOOLS

Clean the sealant nozzle with white spirit.

### IMPORTANT NOTES

Always read the instructions carefully before use.

### STORAGE

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

Store at room temperature.

The shelf life of the product will be at least 2 years.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

### FLAMMABILITY

Extremely flammable.

### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

### SIZES

310ml.

### DISPOSAL

Don't empty any left over product into drains or watercourses.

Your local authority may have special ways to get rid of waste coatings.

Do not pierce or burn the container even after use.

### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control.

### INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

### DATA SHEETS

Data sheets on other Thompson's products are available on request from our Technical Services Department.

