

SELF ADHESIVE FLASHING TAPE

Thompson's Self Adhesive Flashing Tape can be used for general flashing applications, sealing glazing bars and sealing leaks in gutters, down pipes and flat roofs.



THOMPSON'S SELF ADHESIVE FLASHING TAPE:

- Instant waterproofing protection
- Can be applied in damp conditions
- Self Adhesive - quick and easy to use
- Four layers of protection
- Ideal for sealing leaks in gutters, downpipes, roofing and timber joints

TECHNICAL DATA

Storage Life 12 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

For best results, all surfaces must be smooth, clean, dry and dust free. Any loose matter must be removed with a wire brush.

Porous or rough surfaces should be primed using Thompson's Bitumen Primer, which should be allowed to dry before applying Thompson's Self Adhesive Flashing Tape.

APPLICATION

Cut flashing to the required length, remove the release film and press down the adhesive bitumen to the previously prepared surface.

Ensure full contact by smoothing down with a cloth, taking care to eliminate air bubbles.

Final rolling down of the edges with a wallpaper roller will ensure a good edge seal. All overlaps should be a minimum of 25mm and well rolled down.

Note: In cold weather adhesion will be improved by storing the roll in a warm room for 12 hours or more before use, or by gently warming the strip during application. Do not apply below 5°C.

PACKAGING

Sizes:

- 10m x 75mm
- 10m x 100mm
- 10m x 150mm
- 10m x 225mm
- 10m x 300mm
- 3m x 100mm
- 3m x 150mm
- 3m x 225mm

HEALTH AND SAFETY

Thompson's Self Adhesive Flashing Tape is non hazardous in normal conditions of use. Please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.