

MULTI PURPOSE PUTTY

Thompson's Multi Purpose Putty is ideal for bedding and fronting single glass into primed softwood and steel frames.



THOMPSON'S MULTI PURPOSE PUTTY:

- For bedding and fronting single glass into primed softwood and steel frames
- Easy to use
- Excellent durability

TECHNICAL DATA

Storage Life 6 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Ensure all surfaces are clean, dry and free from dust, grease and loose materials. For bare timber or steel, apply one coat of suitable primer and allow to dry.

APPLICATION

Apply a 3mm bead of putty into the rear of the rebate and carefully centre glass in the opening. Secure with clips or pins and finish off with a good sized fillet of putty around the edge of the glass using a putty knife to form a slope.

Clean off any excess material. Finishing should be carried out using a soft brush to ensure complete adhesion.

Leave to allow the putty to form a skin for 7 days and then overcoat with paint within 28 days.

COVERAGE

Apply 6 linear meters of glazing per kilo of putty depending on size of bead.

CLEANING

Immediately after use, all tools should be cleaned with white spirit.

PACKAGING

Sizes: 0.5kg, 1kg, 2kg & 5kg. Available in Natural and Brown

HEALTH AND SAFETY

Thompson's Stabilising Solution is classified as non hazardous. For further information please refer to Health and Safety data sheets available on request. EU limit value for this product (Cat H/h) 50g/L (2007) 30g/L (2010). This product contains maximum 2.5g/L VOC.

LIMITATIONS

Do not use in areas subject to continuous water immersion or swimming pools.

HEALTH AND SAFETY

Thompson's Multi Purpose Putty is non hazardous in normal use. Please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.