

STABILISING SOLUTION

Thompson's Stabilising Solution is a water based treatment which penetrates weathered and dusty surfaces to leave a stable sound base for decoration. It is suitable for both interior and exterior use.



THOMPSON'S STABILISING SOLUTION:

- Stabilises poor surfaces prior to decorating
- For interior and exterior use
- Can be used on brick, stone, masonry, concrete, render and plaster

TECHNICAL DATA

Form	Liquid
Storage Life	12 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Remove all loose and flaking paint, wire brush surfaces to remove any contamination and loose materials which are unsound in depth. Any algae or mould must first be removed by mechanical means or with Thompson's Mould and Mildew Cleaner.

APPLICATION

This is a ready to use product. DO NOT DILUTE. Apply by brush, airless spray or roller in one liberal coat. For extremely porous surfaces, apply a second coat when dry. Drying time 2-4 hours depending on temperature, humidity etc.

Previously painted work may be painted as part of the process but care must be taken to ensure meticulous preparation to avoid "edge lifting". Work painted with gloss coating should not be stabilised with this product.

COVERAGE

5-10m² per Litre depending on porosity of surface and method of application.

CLEANING

Clean equipment with soap and water after use.

PACKAGING

Size: 5L

HEALTH AND SAFETY

Thompson's Stabilising Solution is classified as non hazardous. For further information please refer to Health and Safety data sheets available on request. EU limit value for this product (Cat H/h) 50g/L (2007) 30g/L (2010). This product contains maximum 2.5g/L VOC.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.