

BUTYL GLAZING COMPOUND

Thompson's Butyl Glazing Compound is a non setting compound for use when bead glazing into timber frames. It can also be used on aluminum and steel frames.



THOMPSON'S BUTYL GLAZING COMPOUND:

- Easy to apply
- Suitable for both softwood and hardwood frames
- For interior & exterior use

SPECIFICATIONS

This product must be used in conjunction with Dow Corning 796 when installing sealed units to conform with the requirements of the following:

- BS 8000: Part 7: 1990
- Glass and Glazing Federation Manual Section 4.2
- NHBC Standard 6.7c July 1995

TECHNICAL DATA

Form	Paste
Storage Life	3 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Ensure all surfaces are clean, dry and free from dust, grease and loose materials.

For maximum performance, all timber surfaces to be in contact with Thompson's Butyl Glazing Compound must first be sealed using a timber sealer before applying the compound into the rebate.

APPLICATION

Appropriate distance pieces and setting blocks must be used to ensure sufficient material (3mm-5mm thickness) is present between the frame and glass.

For optimum performance overcoat with paint once a good skin has formed, usually after 7 days.

COVERAGE

Approximately 6 linear meters of glazing per kilogramme of putty, dependant on bead size.

PACKAGING

Size & colour:
2kg Natural

HEALTH AND SAFETY

Thompson's Butyl Glazing Compound is non hazardous in normal use. For further information please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.