

TROWEL APPLIED MASTIC

Thompson's Trowel Applied Mastic is an oil based, pre-mixed compound with silica filler for brick and stone work, pointing and sealing door and window frames. It forms a tack free skin suitable for over painting.



THOMPSON'S TROWEL APPLIED MASTIC:

- Adheres to a wide variety of building substrates
- Ready to use
- Overpaintable
- Available in Red & Stone

TECHNICAL DATA

Storage Life	12 Months unopened stored between 5°C and 25°C in original containers
--------------	---

Specification writers: These values are not intended for use in preparing specifications. Please contact your local Thompson's Sales Representative prior to writing specifications on this product.

SURFACE PREPARATION

Surfaces must be clean, dry and free from loose material and contamination. Apply primer if required. Most substrates only require priming if testing indicates a need, such as timber. Dusty or porous surfaces should be primed with Thompson's Double Boiled Linseed Oil.

APPLICATION

Using a trowel or knife fix the joints/cracks by applying the mastic firmly within the joint. All joints to be securely filled and trowelled off to a smooth finish. Painting can be done after 2 to 3 days.

Any material left in the bucket should be tamped down and covered with polythene to prevent drying out.

COVERAGE

5kg will fill 6m² (9 x 9mm bead width).

CLEANING

Material and tools should be cleaned immediately with white spirit. Hardened sealant can only be removed mechanically.

PACKAGING

Sizes & Colours: 5kg - Red & Stone

LIMITATIONS

Thompson's Trowel Applied Mastic should not be exposed to high levels of chlorine. Do not use in joints wider than 30mm. Do not use in contact with Bitumen, Tar or Aluminium surfaces. Not suitable for surface treated with microporous paints.

HEALTH AND SAFETY

Thompson's Trowel Applied Mastic is non hazardous in normal use. Avoid skin and eye contact. For further information please refer to Health and Safety data sheets available on request.

TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Thompson's Technical Service.

IMPORTANT NOTE The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Thompson's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Thompson's sole warranty is that the product will meet the Thompson's sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Thompson's specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Thompson's disclaims liability for any incidental or consequential damages.