

ROOF & GUTTER SEALANT

Thompson's Roof & Gutter Sealant provides a long lasting highly flexible repair to roof & gutters. It can be used to repair cracks, rips, joints and general leaks and can be applied direct to damp surfaces.

COMPOSITION

A solution of mineral rubber/ binder in a mixed solvent.

AREAS OF APPLICATION

Suitable for use on roofing felt, pipes & guttering.

PREPARATION

Remove dirt or algae with a stiff brush. Pack any deep gaps, if required.

APPLICATION

Cut the nozzle at a 45 degree angle to a width matching the gap you're going to seal. Fit the cartridge into a standard sealant gun. Apply slowly and evenly at an angle to the repair, making sure it covers both sides of the repair. If you're joining gutters, apply sealant to both surfaces and press them together. Smooth down with a wetted spatula. The product may remain tacky after a few hours of application, so don't touch it.

DRYING TIME

The drying time for Thompson's Roof & Gutter Repair will vary dependent upon the nature of the substrate and the thickness of the coating applied. It will however, stop the leak immediately. Allow to dry naturally.

CLEAN UP

All equipment should be cleaner using white spirit.

IMPORTANT NOTES

Always read the instructions carefully before use. Thompsons Roof & Gutter seal should not be used in constant water immersion situations or areas subject to abrasion.

STORAGE

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Store at room temperature. The shelf life of the product is 12 months in unopened containers.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use Shown on the pack. Specific health and safety data sheets Are available on request..

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.



Physical Properties		
Life Expectancy	12-15 Years	
VOC	Very High	>50%
Application Temperature	5°C to 40°C	
Service Temperature	-30°C to +80°C	
Specific Gravity	1.75-1.90	
Appearance	Black viscous liquid	
Odour	Characteristic of bitumen	
Viscosity	Structured	
SPECIFICATIONS		
ISO 9001		
SIZES	310ml	
COLOURS	Black	

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonsweatherproofing.co.uk

Web: www.thompsonsweatherproofing.co.uk

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services